

Foam-in-Place Packaging System



Model 901



Foam output controls, built-in timers and self-diagnostic features continually monitor system performance. All information is reported on the console's easy-to-read message centre.



The Instapak® 901 system features a patented, selfcleaning cartridge dispenser that delivers high quality Instapak® foam.

Total control - optimum performance

Economical

Built-in timers let you control the amount of material used. A series of 10 dispense times can be pre-set to simplify your packaging process.

Flexible

The 901 system can be adjusted (from 2 to 4 kg/min.) to dispense foam at the ideal rate for your application.

Simple

The all electric 901 system can be installed in minutes. No scheduled maintenance is required.

Reliable

The electric pumps, self-diagnostic controls and patented self-cleaning dispenser ensure top quality Instapak® foam.

Safe to use

The 901 system meets all major international product safety standards.



Conforms to all relevant CE directives.

Sealed Air® support services

- Packaging design and testing.
- · Site layout assistance.
- Equipment installation.
- · Operator training.

Specifications

Electrical requirement: 380 - 415 VAC, 16 A,

3 phase, N, earth.

Receptacle type: CEE 17 (5-pole, 16 A).



Sealed Air

Engineered Products Division Telford Way, Kettering, Northants, NN16 8UN, England Tel. +44 (0)1536 315700 - fax +44 (0)1536 410576 www.instapak.com